

XCPTM

PROFESSIONAL

RUST BLOCKERTM

HIGH PERFORMANCE RUST PROTECTION

XCP RUST BLOCKER is a powerful rust prevention spray. It creates a long lasting protective barrier to protect any steel, metal or alloy surface against the effects of rust and corrosion. Use it on exposed metal surfaces, including engine components, suspension units, undercarriage, chrome, chains, electrical connections, motors, shafts, spindles, as well as tools and equipment for shipping and storage, and many more! Provides excellent aluminium protection against galvanic corrosion.

FEATURES:

- **Maximum Protection:** XCP – Xtra Corrosion Protection. For market leading corrosion and rust protection trust the powerful and unique XCP formula to provide long lasting protection against moisture and other corrosive elements.
- **Clear Flexible Film:** The active ingredients in XCP form a clear flexible film that resists cracking.
- **Easy Application:** Can be wiped, sprayed, brushed or used for dipping. The XCP formula, once dry, will provide a soft coating, slightly tacky finish that will provide outstanding corrosion and rust prevention.

APPLICATION AREAS:

- Automotive maintenance
- Bike/motorbike maintenance
- Boating & water sports
- Engineering & industry
- Aviation & aerospace
- Military & firearms
- Fishing tackle and equipment
- Printing equipment & machinery
- Agricultural machinery
- Snow moving equipment
- Garage & workshop
- Home & garden
- Marine & offshore
- Utilities maintenance
- Mining & quarries
- Construction
- Motorhomes/caravans
- Hobbies & crafts
- Plant, equipment & tools
- And many more...

PHYSICAL PROPERTIES:

- **Odour:** solvent odour
- **Appearance:** brown, solution
- **Vapour pressure:** 0.001K Pa
- **Vapour density:** (air = 1) >1.00
- **Melting point:** <20°C / <68°F
- **Dynamic Viscosity @ 25°C / 77°F:** 132 mPa s
- **Kinematic Viscosity 25°C / 77°F:** 148 mm²/s
- **Specific gravity:** 0.9 g/cm³ approx.
- **Flash point:** >100°C / >212°F (CC)
- **Film Thickness:** 15 µm
- **Coverage:** 29 m²/L
- **SILICONE FREE**



COMPATIBILITY AND STORAGE:

XCP RUST BLOCKER is suitable on metal surfaces. Compatibility testing is recommended prior to use for all non-metal and/or coated surfaces. Store at room temperature and not in direct sunlight. Containers should be kept closed and users should consult application notes and material safety data sheet before use. Material safety data sheet is available from your supplier and/or at www.xcp-protection.com.

HANDLING:

Aerosol Spray

- **DANGER:** Extremely flammable aerosol. Pressurised container: may burst if heated. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Repeated exposure may cause skin dryness or cracking. Store at room temperature. Use only as directed.
- HMIS: H-1; F-4; R-0; PP-X

Trigger Spray/Refill Containers

- **DANGER:** May be fatal if swallowed and enters airways. If swallowed: immediately call a poison centre or doctor/physician. Do not induce vomiting. Keep out of reach of children. Dispose of contents/container to an authorised waste point. Repeated exposure may cause skin dryness or cracking. Store at room temperature. Use only as directed.
- HMIS: H-1; F-1; R-0; PP-X

PACKAGING:

- 400ml/13.5 fl oz aerosol can
- 500ml/16.9 fl oz trigger spray bottle
- 5 ltr /1.32 gal refill container

MORE INFORMATION:

 www.xcp-protection.com

 www.facebook.com/xcpprofessional

 www.twitter.com/xcpupro

XCP[™]
PROFESSIONAL

XCP CORROSION TECHNOLOGIES

(A trading division of Marott Graphic Services (UK) Ltd.)

Spott Road Industrial Estate, Dunbar, East Lothian, EH42 1RS, Scotland

T: +44 (0) 1368 862 082 F: +44 (0) 1368 864 491 E: info@xcp-protection.com

www.xcp-protection.com

